


MATERIAL SAFETY DATA SHEET

NFPA Designation 704
DEGREE OF HAZARD
4 = EXTREME
3 = HIGH
2 = MODERATE
1 = SLIGHT
0 = INSIGNIFICANT



May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910, 1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration (Non-Mandatory Form) Form-Approved OMB No. 1218.0072

CHEMICAL NAME

SPOTTER "201"

PRODUCT USAGE

Carpet Spotting Agent

SECTION I

Manufactured For:	Steam Way® International	Emergency Telephone Number:	(303) 355-3566
Address:	4550 Jackson Street	Telephone Number For Information:	(303) 355-3566
City, State, Zip	Denver, Colorado 80216	Date Prepared:	January 13, 1997 Updated: July 22, 2004

SECTION II - Ingredient Information

If component is non-hazardous, specify by * designation. Non-Hazardous means it contains no hazardous ingredients as defined by O.S.H.A. "Hazard Communication" 29CFR 1910.1200. Contains no reportable chemicals under SARA Title III, Sections 311, 312, or 313.		% optional
(Specific Chemical Identity: CAS#)		
"Zonyl" 7950 Fluorosurfactant*	C.A.S. # Mixture	<.5
Sodium Laurel Sulfate*	C.A.S. # 151-21-3	<2.3
Resin*	C.A.S. # 26022-09-3	<.4
Propylene Glycol Methyl Ether*	C.A.S. # 107-98-2	<1.3
Dipropylene Glycol Methyl Ether*	C.A.S. # 034590-94-8	<1.3
Ammonium Hydroxide	C.A.S. # 1336-21-6	<.2
"Zelan" 338 Stain Resist Additive*	C.A.S. # Mixture	<1
Water*	C.A.S. # 7732-18-5	>93

SECTION III - Physical/Chemical Characteristics

Boiling Point	100°C	Specific Gravity (H ₂ O = 1)	1.024
Vapor Pressure (mm Hg.)	17mm Hg	Melting Point	N.A.
Vapor Density (Air=1)	<1	Evaporation Rate (Butyl Acetate=1)	1
Solubility Rate	Full	Percent, Volatile by Volume (%)	N.A.

Appearance and Odor colorless liquid with negligible odor

SECTION IV - Fire and Explosion

Flash Point (Method Used)	N.A.	Flammable Limits	LEL	UEL
Extinguishing Media	N.A.			
Special Fire Fighting Procedures	N.A.			

Unusual Explosion Hazard
N.A.

SECTION V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	None

Incompatibility (Materials to Avoid)

None

Hazardous Decomposition or by-Products

None known

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	N/A

SECTION VI - Health Hazard Data

Health Hazards (Acute and Chronic): Route(s) of Entry/Signs and Symptoms of Exposure

Routes of entry are inhalation, skin contact and ingestion. Non-toxic by ingestion. Prolonged skin contact may cause dryness and irritation of skin. Eye contact may cause irritation. Inhalation of fumes presents no known health hazard.

Emergency and First Aid Procedures

In case of prolonged contact with skin, flush with water for 10 minutes. In case of contact with eyes, flush with water for 15 minutes. If irritation continues, consult a physician. As with all chemicals, use only with adequate ventilation.

Carcinogenicity: NIP? IARC Monographs? OSHA Regulated?

None

Medical Conditions Generally Aggravated by Exposure

None Known

SECTION VII - Precautions For Safe Handling And Use

Steps to be taken in Case Material is Released or Spilled

Pick up excess with an absorbant type material.

Waste Disposal Method

Flush down sewage treatment drain only if in accordance with local, state, and federal regulations.

Precautions To Be Taken In Handling And Storing

Store in a cool dry place between 40°F and 100°F is recommended.

Other Precautions

Do not take internally or inhale vapors. Avoid eye contact.

SECTION VIII - Control Measures

Respiratory Protection (Specific Type)

N/A

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protection Gloves

N/A

Eye Protection

N/A

Other Protective Clothing or Equipment

N/A

Work/Hygienic Practices

N/A